



	W 100 CFi	W 120 CFi	W 130 CFi
Milling drum			
Milling width	1,000 mm	1,200 mm	1,300 mm
Milling depth*	0 to 330 mm		
Drum diameter with tools	980 mm		
Engine			
Manufacturer	CUMMINS		
Type	QSL 9		
Cooling	Water		
Number of cylinders	6		
Rated power at 2,100 rpm	248 kW/333 HP/337 PS		
Maximum power at 1,900 rpm	257 kW/345 HP/350 PS		
Displacement	8.9 l		
Fuel consumption at rated power	67 l/h		
Fuel consumption in field mix	27 l/h		
Exhaust emission standards	EU Stage 4/US Tier 4f		
Electrical system			
Voltage supply	24 V		
Tank capacities			
Fuel tank	610 l		
Addblue®/DEF tank	35 l		
Hydraulic fluid tank	130 l		
Water tank	1,400 l	1,600 l	1,600 l
Driving performance			
Max. milling speed	0 to 43 m/min (2.6 km/h)		
Max. travel speed in wheeled design	0 to 125 m/min (7.5 km/h)		
Max. travel speed in tracked design	0 to 97 m/min (5.8 km/h)		
Wheels or track units			
Wheel size, front and rear (Ø x W)	660 x 280 mm		
Track units, front and rear (L x W x H)	1,330 x 260 x 550 mm		
Loading of the milled material			
Belt width of primary conveyor	650 mm		
Belt width of discharge conveyor	600 mm		
Theoretical capacity of discharge conveyor	176 m³/h		

* = The maximum milling depth may deviate from the value indicated due to tolerances and wear.